



**ASH**

# **SOFNOL ASH**

**Fields of application:** **Polyuretane base of softner for PES and Nylon fabric.**  
**Hydrophilizing agent for goods made of hydrophobic fibres like PES and PP**  
**Increase of wet rubbing fastness and Have a antipilling effect.**

**Composition:** Polyurethane ester derivative

**Appearance:** Clear, yellowish liquid

**Ionic state:** Non-ionic

**pH-value (10 % solution):** Approx. 7

**Density (20 °C):** Approx. 1.0 g/cm<sup>3</sup>

**Viscosity (20 °C):** Approx. 3000 mPa.s

**Solubility:** Readily soluble in water at approx. 20 °C

**Stabilities:** Stable to hard water up to 30 °dH, to acids and alkalis in usual concentrations

**Storage stability:** Approx. 12 months after delivery, if stored in the original unopened drums under the stated conditions

**Storage conditions:** Recommended storage temperature: + 3 °C to + 35 °C

**Packing:** Drum, container

Factory and Office : Jl. Cikuya Tonggoh No.77 Ds.Lagadar, Kec.Margaasih, Kab.Bandung -Jawa Barat-Indonesia  
Phone 022.667.64.19 Fax : 022.667.64.29  
Head Office : Jl. Setrasari V No 17 Bandung Phone 022.200.15.66 Fax : 022.200.15.67