

## **HYPERET WK**

| Fields of application:    | Non-slip agent for all types of fibres  |
|---------------------------|---|
|                           |   |
| Composition:              | Combination of silicic acid sol and amine acetates  |
| Appearance:               | Light beige, opal liquid  |
| Ionic state:              | Cation-active   |
| pH-value (10 % solution): | Approx. 4   |
| Density (20 °C):          | Approx. 1.1 g/cm <sup>3</sup>   |
| Viscosity (20 °C):        | Approx. 10 mPa.s  |
| Solubility:               | Readily soluble in water at approx. 20°C  |
| Stabilities:              | Stable to hard water up to 40° dH. Stable to acids in usual concentrations. Sensitive to alkalis.     |
| Storage stability:        | Approx. 6 months after delivery, if stored in the original unopened drums under the stated conditions |
| Storage conditions:       | Do not store product below + 3 °C and above + 35 °C Cannot be used after exposure to frost            |
| Packing:                  | Drum, container   |

Factory and Office : Jl. Cikuya Tonggoh No.77 Ds.Lagadar, Kec.Margaasih, Kab.Bandung -Jawa Barat-Indonesia Phone 022.667.64.19 Fax : 022.667.64.29 Head Office : Jl. Setrasari V No 17 Bandung Phone 022.200.15.66 Fax : 022.200.15.67