



LBC sp LBC conc

# HYBRICANT LBC sp. LBC conc

**Fields of application:** Special friction-free crease preventing lubricant on jet dyeing M/C, for Rayon span, Cotton mercerizing, Tencel, Polynosic. Also obtain product excellent less-filing quality goods.

<b>Composition:</b>	Polycarbonic acid derivative
<b>Appearance:</b>	Colourless, clear to slightly turbid liquid
<b>Ionic state:</b>	Anion active
<b>pH-value (10 % solution):</b>	Approx. 7 - 8
<b>Density (at 20 °C):</b>	Approx. 1.0 g/cm <sup>3</sup>
<b>Viscosity (at 20 °C):</b>	Approx. 10 mPa.s
<b>Solubility:</b>	With cold water
<b>Stabilities:</b>	Highly stable to acid, alkali and electrolyte
<b>Storage stability:</b>	Approx. 12 months after delivery, if stored in the original unopened drums under the stated conditions
<b>Storage conditions:</b>	Recommended storage temperature: + 3 °C to + 35 °C
<b>Packing:</b>	Drum, container

Factory and Office : Jl. Cikuya Tonggoh No.77 Ds.Lagadar, Kec.Margaasih, Kab.Bandung -Jawa Barat-Indonesia  
Phone 022.667.64.19 Fax : 022.667.64.29  
Head Office : Jl. Setrasari V No 17 Bandung Phone 022.200.15.66 Fax : 022.200.15.67