

HYBRAN CPOS

Fields of application: Main applications are one-bath dyeing of

PES, T/C, T/R with spandex blended fabric which want to anti-contamination in M/C & surface fabric from spandex oil. It's also have got excellent lubricant effect for polyester fabric and soil-release effect.

Composition: Terapthalate-polyglykol-polycondensate

Appearance: Turbid liquid

Ionic state: Non-ionic

pH-value (10% solution in dist. water) Approx. 5.0~6.0

Density (20 °C): Approx. 1.35 g/cm³

Viscosity (20 °C): Approx. 300 mPa.s

Solubility: In cold water

Stabilities: Stable to hard water, electrolytes, acids and alkalis in

concentrations usual in pretreatment and dyeing

Storage stability: In originally sealed drums 6 months from delivery under stated

conditions

Storage conditions: Keep drum closed thoroughly. Recommended storage

temperature +3°C to +35°C.

Packing: Polyethylene drums or Iron drum

Factory and Office: Jl. Cikuya Tonggoh No.77 Ds.Lagadar, Kec.Margaasih, Kab.Bandung -Jawa Barat-

Indonesia Phone 022.667.64.19 Fax: 022.667.64.29

Head Office: Jl. Setrasari V No 17 Bandung Phone 022.200.15.66 Fax: 022.200.15.67