

# DYEFIX PRE

<b>Fields of application:</b>	<b>Aftertreating agent for the improvement of wet fastness properties of PA dyed with acid and metal complex dyestuffs</b>
<b>Composition:</b>	Dark brown, clear-slightly cloudy, liquid
<b>Appearance:</b>	Dark-brown liquid
<b>Ionic state:</b>	Anion-active
<b>pH-value (10 % solu. i.d.w.):</b>	Approx. 5.0
<b>Density (at 20 °C):</b>	Approx. 1.2 g/cm <sup>3</sup>
<b>Viscosity (at 20 °C):</b>	Approx. 75 mPa.s
<b>Solubility:</b>	In cold water
<b>Stabilities:</b>	Stable under standard dyeing conditions for PA/cellulose,
<b>Storage stability:</b>	In originally sealed drums, about one year from delivery under stated conditions
<b>Storage conditions:</b>	Recommended storage temperature: + 3 °C to + 35 °C
<b>Packing:</b>	Polyethylen drums

Factory and Office : Jl. Cikuya Tonggoh No.77 Ds.Lagadar, Kec.Margaasih, Kab.Bandung -Jawa Barat-Indonesia Phone 022.667.64.19 Fax : 022.667.64.29  
Head Office : Jl. Setrasari V No 17 Bandung Phone 022.200.15.66 Fax : 022.200.15.67