



LEV cc

## LEVELON LEV cc

<b>Fields of application:</b>	Very low-foaming levelling agent and a very good migration effect, promotes the synchronous absorption of disperse dyes in the heating-up phase
<b>Composition:</b>	Carboxylic acid ethoxylate and aryl sulphonate
<b>Appearance:</b>	Light Brown, low-viscous, liquid
<b>Ionic state:</b>	Anionic
<b>pH value (10 % solution):</b>	Approx. 6.5
<b>Density (at 20 °C):</b>	Approx. 1.1 g/cm <sup>3</sup>
<b>Viscosity (at 20 °C):</b>	Approx. 100 mPa.s
<b>Solubility:</b>	In cold or warm water
<b>Stabilities:</b>	High resistance to acids, alkali, electrolytes and hardness
<b>Storage stability:</b>	Approx. 12 months after delivery if stored in the original unopened drums under the stated conditions
<b>Storage conditions:</b>	Recommended storage temperature: +3 °C to +35 °C
<b>Packing:</b>	Drum, container

**Factory and Office : Jl. Cikuya Tonggoh No.77 Ds.Lagadar, Kec.Margaasih, Kab.Bandung -Jawa Barat-Indonesia Phone 022.667.64.19 Fax : 022.667.64.29**  
**Head Office : Jl. Setrasari V No 17 Bandung Phone 022.200.15.66 Fax : 022.200.15.67**